


Tonale Boucle

Technical specifications

Composition	88% PP 12% PL
Grammage (g/m2)	658
Abrasion resistance (Martindale)	30.000 cycles ISO 12947-2
Pilling	4 5.000 rubs ISO 12945-2
Lightfastness	7/8 UNI EN ISO 105-B02
Seam slippage warp/weft (mm)	4 UNI EN ISO 13936-2
Seam slippage weft/warp (mm)	2 UNI EN ISO 13936-2
Colour fastness rubbing dry / wet	4/5 / 4 UNI EN ISO 105-X12
Tensile strength weft & warp (N)	848 / 2.187 UNI EN ISO 13934-1 Elongation 49% / 42%
Cigarette test	Pass BS 5852 sez.4 part.1
Colour fastness washing change & stain	4 UNI EN ISO 105-C06
Colour fastness to artificial weather	7 UNI EN ISO 105-B04
Colour fastness chlorine water	4 UNI EN ISO 105-E03
Colour fastness to sea water	4/5 UNI EN ISO 105-E02
Tear force wingshape weft/warp (N)	284 / 213 UNI EN ISO 13937-3
Burning resistance upholstery furniture	Pass TB 117:2013 section 1

Colours




White Poppy
81L




Sesame
82L



Anise
83L



Dill
84L



Allspice Jamaica
85L



Bird's foot
86L